



SIMATIC S7-1200, Analog input, SM 1231 TC, 4 AI thermocouples

Figure similar

| General information | |
|---|--|
| Product type designation | SM 1231, AI 4x16 bit TC |
| Supply voltage | |
| Rated value (DC) | 24 V |
| Input current | |
| Current consumption, typ. | 40 mA |
| from backplane bus 5 V DC, typ. | 80 mA |
| Power loss | |
| Power loss, typ. | 1.5 W |
| Analog inputs | |
| Number of analog inputs | 4; Thermocouples |
| permissible input voltage for voltage input (destruction limit), max. | ±35 V |
| Technical unit for temperature measurement adjustable | Degrees Celsius/degrees Fahrenheit |
| Input ranges | |
| <ul style="list-style-type: none"> • Voltage • Current • Thermocouple • Resistance thermometer • Resistance | Yes No Yes; J, K, T, E, R, S, N, C, TXK/XK(L); voltage range: ±80 mV No No |
| Input ranges (rated values), voltages | |
| <ul style="list-style-type: none"> • -80 mV to +80 mV — Input resistance (-80 mV to +80 mV) | Yes ≥1 MOhm |
| Input ranges (rated values), thermocouples | |
| <ul style="list-style-type: none"> • Type B • Type C • Type E • Type J • Type K • Type N • Type R • Type S • Type T • Type TXK/TXK(L) to GOST | Yes Yes Yes Yes Yes Yes Yes Yes Yes Yes |
| Thermocouple (TC) | |
| Temperature compensation | |
| — parameterizable | No |
| Analog value generation for the inputs | |
| Measurement principle | integrating |

| | |
|---|--|
| Integration and conversion time/resolution per channel | |
| <ul style="list-style-type: none"> Resolution with overrange (bit including sign), max. Integration time, parameterizable Interference voltage suppression for interference frequency f_1 in Hz | 15 bit; + sign No 85 dB at 50 / 60 / 400 Hz |
| Smoothing of measured values | |
| <ul style="list-style-type: none"> parameterizable | Yes |
| Errors/accuracies | |
| Temperature error (relative to input range), (+/-) | 25 °C $\pm 0.1\%$, to 55 °C $\pm 0.2\%$ total measurement range |
| Repeat accuracy in steady state at 25 °C (relative to output range), (+/-) | 0.5 % |
| Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$, $f_1 =$ interference frequency | |
| <ul style="list-style-type: none"> Common mode interference, min. | 120 dB |
| Interrupts/diagnostics/status information | |
| Alarms | Yes |
| Diagnostics function | Yes; Can be read out |
| Alarms | |
| <ul style="list-style-type: none"> Diagnostic alarm | Yes |
| Diagnoses | |
| <ul style="list-style-type: none"> Monitoring the supply voltage Wire-break | Yes Yes |
| Diagnostics indication LED | |
| <ul style="list-style-type: none"> for status of the inputs for maintenance | Yes Yes |
| Degree and class of protection | |
| IP degree of protection | IP20 |
| Standards, approvals, certificates | |
| CE mark | Yes |
| CSA approval | Yes |
| UL approval | Yes |
| cULus | Yes |
| FM approval | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| Marine approval | Yes |
| Ecological footprint | |
| <ul style="list-style-type: none"> environmental product declaration | Yes |
| Global warming potential | |
| — global warming potential, (total) [CO ₂ eq] | 43.1 kg |
| — global warming potential, (during production) [CO ₂ eq] | 7.62 kg |
| — global warming potential, (during operation) [CO ₂ eq] | 36 kg |
| — global warming potential, (after end of life cycle) [CO ₂ eq] | -0.544 kg |
| Ambient conditions | |
| Free fall | |
| <ul style="list-style-type: none"> Fall height, max. | 0.3 m; five times, in product package |
| Ambient temperature during operation | |
| <ul style="list-style-type: none"> min. max. horizontal installation, min. horizontal installation, max. vertical installation, min. vertical installation, max. | -20 °C 60 °C -20 °C 60 °C -20 °C 50 °C |
| Ambient temperature during storage/transportation | |
| <ul style="list-style-type: none"> min. max. | -40 °C 70 °C |
| Air pressure acc. to IEC 60068-2-13 | |
| <ul style="list-style-type: none"> Operation, min. Operation, max. Storage/transport, min. | 795 hPa 1 080 hPa 660 hPa |

| | |
|---|--|
| • Storage/transport, max. | 1 080 hPa |
| Relative humidity | |
| • Operation at 25 °C without condensation, max. | 95 % |
| Pollutant concentrations | |
| • SO2 at RH < 60% without condensation | SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free |
| connection method | |
| required front connector | Yes |
| Mechanics/material | |
| Enclosure material (front) | |
| • Plastic | Yes |
| Dimensions | |
| Width | 45 mm |
| Height | 100 mm |
| Depth | 75 mm |
| Weights | |
| Weight, approx. | 180 g |

last modified: 10/9/2024 