



Figure similar

TERMINAL BLOCK TP1 W/O LED PUSH-IN TERM.

Connection module TP1 8 channels u. 2x2 terminals f. Potential supply Type: Push-in terminal without LED, VPE=1 unit 16 pole IDC connector f. cable

| | |
|--|--|
| target system | SIMATIC S7-300 / 1500 |
| suitability for use | Digital I/O modules |
| product type designation | Fully modular connection |
| product designation | Connection module |
| electrical data | |
| operating voltage | |
| • at DC / rated value | 24 V |
| • rated value | 50 V |
| • at DC / maximum | 50 V |
| ampacity / per pin / maximum | 1 A |
| continuous current / at DC / per signal cable / maximum | 1 A |
| total current / maximum | 4 A |
| product component / PE connection | No |
| product component / shield connection | No |
| product component / disconnecter | No |
| product function / infeed function | Yes |
| product feature / cross-connectable | No |
| connection method | |
| number of terminals | 12; 8 x I/O; 2 x L+, 2 x M |
| number of channels | 8 |
| number of terminal levels | 1 |
| type of connecting terminal | push-in |
| position / of the terminal | Top |
| type of electrical connection / for connecting cable | Plug-in connection |
| number of cables / per connection | 2; Connection for internal system: Combination of 1 or 2 Wires until the sum total of cross sections be achieved in a ferrule. |
| design of terminal / terminal levels internally linked | No |
| type of connectable conductor cross-sections / solid | No |
| connectable conductor cross-section | |
| • for flexible conductor / with core end processing | 0.2 ... 2.5 mm ² ; End sleeve according to DIN 46228/1 or DIN 46228/4 with plastic collar |
| • stranded | 0.2 ... 2.5 mm ² |
| • finely stranded / without core end processing | 0.2 ... 2.5 mm ² |
| • finely stranded / with core end processing | 0.2 ... 2.5 mm ² |
| number of poles / at the 1st interface | 16; IDC connector with installed strain relief for the connecting cable |
| number of the plug contacts / of the electrical connection | 1 |
| wire length / maximum | 30 m; between front connector module and Connection module |
| width of screwdriver blade | 3.5 mm |
| standards, specifications, approvals | |
| certificate of suitability | |

| | |
|--|-----|
| • cULus approval | Yes |
| design tested acc. to type of protection / EEx e | No |
| overvoltage category | 2 |
| degree of pollution | 2 |
| combustibility class according to UL 94 | V1 |

standards, specifications, approvals / Environmental Product Declaration

| | |
|-----------------------------------|---------|
| Environmental Product Declaration | Yes |
| Global Warming Potential [CO2 eq] | |
| • total | 11.1 kg |
| • during manufacturing | 0.4 kg |
| • during operation | 10.7 kg |
| • after end of life | 0.04 kg |

ambient conditions

| | |
|---------------------|----------------|
| ambient temperature | |
| • during operation | 0 ... 60 °C |
| • during storage | -40 ... +70 °C |

mechanical data

| | |
|--|--------------------------------|
| width × height × depth | 40 mm × 58 mm × 50 mm |
| mounting type | DIN rail 35 mm, DIN rail 15 mm |
| mounting position | any |
| height / with lowest-profile installation | 50 mm |
| net weight | 0.05 kg |
| insulation material | other |
| color | |
| • of the enclosure | grey |
| • of the light source | without |
| product component / required / end cover plate | No |

further information / internet links

| | |
|---|---|
| internet link | |
| • to website: Industry Mall | https://mall.industry.siemens.com |
| • to web page: selection aid TIA Selection Tool | https://www.siemens.com/tstcloud |
| • to web page: system cabling | https://siemens.com/simatic-top-connect |
| • to website: CAx-Download-Manager | https://siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |

additional information

| | |
|-------------------|---|
| other information | Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified) |
| marketing text | The TP1 connection module for a 1-wire connection with 8 channels and a potential connection with push-in terminals without LED for signalling forms the interface between the connection cables of the peripherals coming from the field and the SIMATIC S7. This is mounted on the DIN rail and is exactly adapted to the respective task thanks to its functionality with push-in terminals. This connection module is part of the fully modular SIMATIC TOP connect connection for the fastest and safest system cabling. In addition to low wiring costs, error sources in cabling can be significantly reduced. Sensors and actuators from the peripherals are combined with the connection modules of SIMATIC TOP connect and connected to the SIMATIC S7-300/1500 via cable and front plug-in module. |

Classifications

| | Version | Classification |
|--------|---------|----------------|
| eClass | 14 | 27-25-01-12 |
| eClass | 12 | 27-14-11-28 |
| eClass | 9.1 | 27-14-11-28 |
| eClass | 9 | 27-14-11-28 |
| eClass | 8 | 27-14-11-28 |
| eClass | 7.1 | 27-14-11-28 |
| eClass | 6 | 27-14-11-28 |
| ETIM | 9 | EC000900 |
| ETIM | 8 | EC000900 |
| ETIM | 7 | EC000900 |
| UNSPSC | 15 | 39-12-14-10 |

Approvals / Certificates

| | | |
|--------------------------|-----|-------------|
| General Product Approval | EMV | Environment |
|--------------------------|-----|-------------|

[Manufacturer Declaration](#)



last modified:

1/18/2025 