



SIMATIC S7-400, analog input SM 431, isolated 16 AI; resolution 16 bit, U/I/Resistor/Thermocouple/Pt100 , alarm, diagnostics

Figure similar

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> Rated value (DC) 	24 V; Only required for supplying 2-wire transmitters
<ul style="list-style-type: none"> Reverse polarity protection 	Yes
Input current	
from load voltage L+ (without load), max.	400 mA; for 16 connected, fully controlled 2-wire transmitters
from backplane bus 5 V DC, max.	700 mA
Power loss	
Power loss, typ.	4.5 W
Analog inputs	
Number of analog inputs	16
<ul style="list-style-type: none"> For voltage/current measurement 	16
<ul style="list-style-type: none"> For resistance measurement 	8
permissible input voltage for voltage input (destruction limit), max.	18 V; 18 V continuous, 75 V for 1 ms (mark to space ratio 1:20)
permissible input current for current input (destruction limit), max.	40 mA
Constant measurement current for resistance-type transmitter, typ.	1.67 mA
Input ranges	
<ul style="list-style-type: none"> Voltage 	Yes
<ul style="list-style-type: none"> Current 	Yes
<ul style="list-style-type: none"> Thermocouple 	Yes
<ul style="list-style-type: none"> Resistance thermometer 	Yes
<ul style="list-style-type: none"> Resistance 	Yes
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> 1 V to 5 V <ul style="list-style-type: none"> Input resistance (1 V to 5 V) 	Yes 1 MΩ
<ul style="list-style-type: none"> -1 V to +1 V <ul style="list-style-type: none"> Input resistance (-1 V to +1 V) 	Yes 1 MΩ
<ul style="list-style-type: none"> -10 V to +10 V <ul style="list-style-type: none"> Input resistance (-10 V to +10 V) 	Yes 1 MΩ
<ul style="list-style-type: none"> -2.5 V to +2.5 V <ul style="list-style-type: none"> Input resistance (-2.5 V to +2.5 V) 	Yes 1 MΩ
<ul style="list-style-type: none"> -25 mV to +25 mV <ul style="list-style-type: none"> Input resistance (-25 mV to +25 mV) 	Yes 1 MΩ
<ul style="list-style-type: none"> -250 mV to +250 mV <ul style="list-style-type: none"> Input resistance (-250 mV to +250 mV) 	Yes 1 MΩ
<ul style="list-style-type: none"> -5 V to +5 V <ul style="list-style-type: none"> Input resistance (-5 V to +5 V) 	Yes 1 MΩ

- -50 mV to +50 mV
 - Input resistance (-50 mV to +50 mV) 1 MΩ
- -500 mV to +500 mV
 - Input resistance (-500 mV to +500 mV) 1 MΩ
- -80 mV to +80 mV
 - Input resistance (-80 mV to +80 mV) 1 MΩ

Input ranges (rated values), currents

- 0 to 20 mA
 - Input resistance (0 to 20 mA) 50 Ω
- -10 mA to +10 mA
 - Input resistance (-10 mA to +10 mA) 50 Ω
- -20 mA to +20 mA
 - Input resistance (-20 mA to +20 mA) 50 Ω
- 4 mA to 20 mA
 - Input resistance (4 mA to 20 mA) 50 Ω
- -5 mA to +5 mA
 - Input resistance (-5 mA to +5 mA) 50 Ω

Input ranges (rated values), thermocouples

- Type B
 - Input resistance (Type B) 1 MΩ
- Type E
 - Input resistance (Type E) 1 MΩ
- Type J
 - Input resistance (type J) 1 MΩ
- Type K
 - Input resistance (Type K) 1 MΩ
- Type L
 - Input resistance (Type L) 1 MΩ
- Type N
 - Input resistance (Type N) 1 MΩ
- Type R
 - Input resistance (Type R) 1 MΩ
- Type S
 - Input resistance (Type S) 1 MΩ
- Type T
 - Input resistance (Type T) 1 MΩ
- Type U
 - Input resistance (Type U) 1 MΩ

Input ranges (rated values), resistance thermometer

- Ni 100
 - Input resistance (Ni 100) 1 MΩ
- Ni 1000
 - Input resistance (Ni 1000) 1 MΩ
- Pt 100
 - Input resistance (Pt 100) 1 MΩ
- Pt 1000
 - Input resistance (Pt 1000) 1 MΩ
- Pt 200
 - Input resistance (Pt 200) 1 MΩ
- Pt 500
 - Input resistance (Pt 500) 1 MΩ

Input ranges (rated values), resistors

- 0 to 48 ohms
 - Input resistance (0 to 48 ohms) 1 MΩ
- 0 to 150 ohms
 - Input resistance (0 to 150 ohms) 1 MΩ
- 0 to 300 ohms
 - Input resistance (0 to 300 ohms) 1 MΩ
- 0 to 600 ohms
 - Input resistance (0 to 600 ohms) 1 MΩ
- 0 to 6000 ohms
 - Input resistance (0 to 6000 ohms) Yes; Usable up to 5000 Ohm

— Input resistance (0 to 6000 ohms)	1 MΩ
Thermocouple (TC)	
Temperature compensation	
— parameterizable	Yes
— external temperature compensation with Pt100	Yes
— external temperature compensation with compensations socket	Yes
— dynamic reference temperature value	Yes
Characteristic linearization	
● parameterizable	Yes
— for thermocouples	Type B, E, J, K, L, N, R, S, T, U
— for resistance thermometer	Pt100, Pt200, Pt500, Pt1000, Ni100, Ni1000
Cable length	
● shielded, max.	200 m; 50 m with thermocouples and input ranges ≤ 80 mV
Analog value generation for the inputs	
Integration and conversion time/resolution per channel	
● Resolution with overrange (bit including sign), max.	16 bit; 16 / 16 / 16
● Integration time, parameterizable	Yes
● Basic conversion time (ms)	6 / 20,1 / 23,5 ms
● Integration time (ms)	2,5 / 16,7 / 20 ms
● Interference voltage suppression for interference frequency f1 in Hz	400 / 60 / 50 Hz
Encoder	
Connection of signal encoders	
● for voltage measurement	Yes; possible
● for current measurement as 2-wire transducer	Yes
● for current measurement as 4-wire transducer	Yes
● for resistance measurement with two-wire connection	Yes; Line resistances are also measured
● for resistance measurement with three-wire connection	Yes
● for resistance measurement with four-wire connection	Yes
Errors/accuracies	
Temperature error (relative to input range), (+/-)	0.004 %/K
Operational error limit in overall temperature range	
● Voltage, relative to input range, (+/-)	0.3 %; ±0.3 % at ±250 mV, ±500 mV, ±1 V, ±2.5 V, ±5 V, 1 to 5 V, ±10 V; ±0.31 % at ±80 mV; ±0.32 % at ±50 mV; ±0.35 % at ±25 mV
● Current, relative to input range, (+/-)	0.3 %; at 0 to 20 mA, ±5 mA, ±10 mA, ±20 mA, 4 to 20 mA
● Resistance, relative to input range, (+/-)	0.3 %; ±0.3% at 0 to 48 Ohm (4-conductor measurement), 0 to 150 Ohm (4-conductor measurement), 0 to 300 Ohm (4-conductor measurement), 0 to 600 Ohm (4-conductor measurement), 0 to 5000 Ohm (4-conductor measurement, in range of 6000 Ohm); ±0.4% at 0 to 300 Ohm (3-conductor measurement), 0 to 600 Ohm (3-conductor measurement), 0 to 5000 Ohm (3-conductor measurement, in range of 6000 Ohm);
● Resistance thermometer, relative to input range, (+/-)	0.4 %
● Thermocouple, relative to input range, (+/-)	TC Type B (±11.5 K), TC Type R (±7.3 K), TC Type S (±8.3 K), TC Type T (±1.7 K), TC Type E (±3.2 K), TC Type J (±4.3 K), TC Type K (±6.2 K), TC Type U (±2.8 K), TC Type L (±4.2 K), TC Type N (±4.4 K)
Basic error limit (operational limit at 25 °C)	
● Voltage, relative to input range, (+/-)	0.15 %; ±0.15% at ±250 mV, ±500 mV, ±1 V, ±2.5 V, ±5 V, 1 V to 5 V, ±10 V; ±0.17% at ±80 mV; ±0.19% at ±50 mV; ±0.23% at ±25 mV
● Current, relative to input range, (+/-)	0.15 %; at 0 to 20 mA, ±5 mA, ±10 mA, ±20 mA, 4 to 20 mA
● Resistance, relative to input range, (+/-)	0.15 %; ±0.15 % at 0 to 48 ohms (4-conductor measurement), 0 to 150 ohms (4-conductor measurement), 0 to 300 ohms (4-conductor measurement), 0 to 5000 ohms (4-conductor measurement, in range of 6000 ohms); ±0.3 % at 0 to 300 ohms (3-conductor measurement), 0 to 600 ohms (3-conductor measurement), 0 to 5000 ohms (3-conductor measurement, in range of 6000 ohms)
● Resistance thermometer, relative to input range, (+/-)	0.3 %
● Thermocouple, relative to input range, (+/-)	TC Type B (±7.6 K), TC Type R (±4.8 K), TC Type S (±5.4 K), TC Type T (±1.1 K), TC Type E (±1.8 K), TC Type J (±2.3 K), TC Type K (±3.4 K), TC Type U (±1.7 K), TC Type L (±2.3 K), TC Type N (±2.6 K)
Interrupts/diagnostics/status information	
Diagnostics function	Yes; Parameterizable
Alarms	
● Diagnostic alarm	Yes; Parameterizable
● Limit value alarm	Yes; Parameterizable
● Hardware interrupt	Yes; Parameterizable

Diagnoses	
• Diagnostic information readable	Yes
Diagnostics indication LED	
• internal fault INTF (red)	Yes
• external fault EXTF (red)	Yes
Potential separation	
Potential separation analog inputs	
• Potential separation analog inputs	Yes; internal/external
• between the channels	No
• between the channels and backplane bus	Yes
• Between the channels and load voltage L+	Yes
Isolation	
Isolation tested with	2 120 V DC between bus and L+/M; 2 120 V DC between bus and analog section; 500 V DC between bus and local ground; 500 V DC between analog section and L+/M; 2 120 V DC between analog section and local ground; 2 120 V DC between L+/M and local ground
Dimensions	
Width	25 mm
Height	290 mm
Depth	210 mm
Weights	
Weight, approx.	500 g

Classifications			
		Version	Classification
	eClass	14	27-24-22-01
	eClass	12	27-24-22-01
	eClass	9.1	27-24-22-01
	eClass	9	27-24-22-01
	eClass	8	27-24-22-01
	eClass	7.1	27-24-22-01
	eClass	6	27-24-22-01
	ETIM	9	EC001420
	ETIM	8	EC001420
	ETIM	7	EC001420
	IDEA	4	3562
	UNSPSC	15	32-15-17-05

Approvals / Certificates

General Product Approval



[Manufacturer Declaration](#)

[Miscellaneous](#)



[KC](#)

General Product Approval

EMV

For use in hazardous locations

[Metrological Approval](#)



For use in hazardous locations

Marine / Shipping

[EM](#)



[Type Examination Certificate](#)



Marine / Shipping



[NK / Nippon Kaiji Kyokai](#)



Marine / Shipping



[CCS \(China Classification Society\)](#)

last modified:

12/8/2024