



SIMATIC S7-400, power supply PS405: 10 A, wide range, 24/48/60 V DC; 5 V DC/10 A, for redundant use

Supply voltage

Rated value (DC)

• 24 V DC	Yes
• 48 V DC	Yes
• 60 V DC	Yes

Mains buffering

• Mains/voltage failure stored energy time	20 ms
• Mains buffering according to NAMUR recommendation	Yes

Input current

Rated value at 24 V DC	4 A
Rated value at 48 V DC	2 A
Rated value at 60 V DC	1.6 A
Inrush current, max.	18 A; Full width at half maximum 20 ms

output voltage / header

Type of output voltage	DC
Rated value (DC)	
• 5 V DC	Yes
• 24 V DC	Yes

Output current

for backplane bus (5 V DC), max.	10 A; no base load required
for backplane bus (24 V DC), max.	1 A; idling-proof
Short-circuit protection	Yes

Power

Active power input, typ.	95 W
--------------------------	------

Power loss

Power loss, typ.	20 W
------------------	------

Battery

Backup battery	
• Backup battery (optional)	Yes; 2x lithium AA; 3.6 V / 2.2 Ah

Hardware configuration

Slots	
• required slots	2

Potential separation

primary/secondary	Yes
-------------------	-----

Isolation

Overvoltage category	II
----------------------	----

Degree and class of protection

Equipment protection class	I, with protective conductor
----------------------------	------------------------------

Standards, approvals, certificates

FM approval	Yes; Ta: 0 °C to 60 °C T4
-------------	---------------------------

CCC	Yes
BIS	Yes
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	60 °C
connection method	
Design of electrical connection	3x 1.5 mm ² , solid or stranded wire with end sleeve, external diameter 3 mm to 9 mm
Dimensions	
Width	50 mm
Height	290 mm
Depth	217 mm
Weights	
Weight, approx.	1 200 g
Classifications	

	Version	Classification
eClass	14	27-24-22-09
eClass	12	27-24-22-09
eClass	9.1	27-24-22-09
eClass	9	27-24-22-09
eClass	8	27-24-22-09
eClass	7.1	27-24-22-09
eClass	6	27-24-22-09
ETIM	9	EC000599
ETIM	8	EC000599
ETIM	7	EC000599
IDEA	4	3575
UNSPSC	15	32-15-17-06

Approvals / Certificates

General Product Approval



[Miscellaneous](#)



[KC](#)



EMV

For use in hazardous locations



[FM](#)



For use in hazardous locations

Maritime application



[Type Examination Certificate](#)



Maritime application



[NK / Nippon Kaiji Kyokai](#)



[CCS \(China Classification Society\)](#)



last modified:

6/7/2025 