



SIMATIC S7-400, interface module Send IM 460-0 for central coupling without PS transfer, with C-bus

Figure similar

Input current	
from backplane bus 5 V DC, max.	140 mA
Power loss	
Power loss, max.	700 mW
Hardware configuration	
Cable length between first and last interface module, max.	5 m
connection method	
termination plug	6ES7461-0AA0-7AA0
Dimensions	
Width	25 mm
Height	290 mm
Depth	280 mm
Weights	
Weight, approx.	600 g
Classifications	

	Version	Classification
eClass	14	27-24-22-08
eClass	12	27-24-22-08
eClass	9.1	27-24-22-08
eClass	9	27-24-22-08
eClass	8	27-24-22-08
eClass	7.1	27-24-22-08
eClass	6	27-24-22-08
ETIM	9	EC001423
ETIM	8	EC001423
ETIM	7	EC001423
IDEA	4	3564
UNSPSC	15	32-15-17-05

Approvals / Certificates
General Product Approval

[Miscellaneous](#)



[KC](#)



EMV		For use in hazardous locations								
	RCM		RCM		IECEX		ATEX	FM		CCC
For use in hazardous locations					Maritime application					
	IECEX	Type Examination Certificate		ATEX		ABS		BUREAU VERITAS		DNV
Maritime application										
	LRS	NK / Nippon Kaiji Kyokai		PRS		RINA		RMRS	CCS (China Classification Society)	

last modified: 6/7/2025 