

product type designation

CM 1542-5

communications module CM 1542-5 for connection of S7-1500 to PROFIBUS DP, DPV1 master or DP slave, S7 and PG/OP communication, data record routing, time-of-day synchronization, diagnostic



transfer rate

transfer rate

- at the 1st interface / according to PROFIBUS 9.6 kbit/s ... 12 Mbit/s

interfaces

number of interfaces / according to Industrial Ethernet

0

number of electrical connections

- at the 1st interface / according to PROFIBUS 1

type of electrical connection

- at the 1st interface / according to PROFIBUS 9-pin Sub-D socket (RS485)

supply voltage, current consumption, power loss

type of voltage / of the supply voltage

DC

supply voltage / 1 / from backplane bus

15 V

relative symmetrical tolerance / at DC

- at 15 V 3 %

consumed current

- from backplane bus / at DC / at 15 V / typical 0.2 A

power loss [W]

3 W

ambient conditions

ambient temperature

- for vertical installation / during operation 0 ... 40 °C
- for horizontally arranged busbars / during operation 0 ... 60 °C
- during storage -40 ... +70 °C
- during transport -40 ... +70 °C

relative humidity

- at 25 °C / without condensation / during operation / maximum 95 %

protection class IP

IP20

design, dimensions and weights

module format

Compact module S7-1500 single width

width

35 mm

height

142 mm

depth

129 mm

net weight

0.4 kg

fastening method

- S7-1500 rail mounting Yes

product features, product functions, product components / general

number of units

- per CPU / maximum 8
- note depending on CPU type

performance data / open communication	
number of possible connections / for open communication / by means of SEND/RECEIVE blocks / maximum	30
data volume	
as user data per connection / for open communication / by means of SEND/RECEIVE blocks / maximum	240 byte
performance data / PROFIBUS DP	
service / as DP master	
DPV1	Yes
number of DP slaves	
on DP master / operable	125
data volume	
of the address range of the inputs / as DP master / total	8192 byte
of the address range of the outputs / as DP master / total	8192 byte
of the address range of the inputs / per DP slave	244 byte
of the address range of the outputs / per DP slave	244 byte
service / as DP slave	
DPV0	Yes
DPV1	Yes
data volume	
of the address range of the inputs / as DP slave / total	240 byte
of the address range of the outputs / as DP slave / total	240 byte
performance data / S7 communication	
number of possible connections / for S7 communication	
maximum	48; depending on the system upper limit
performance data / multi-protocol mode	
number of active connections / with multi-protocol mode	48
performance data / telecontrol	
protocol / is supported	
TCP/IP	No
product functions / management, configuration, engineering	
configuration software	
required	STEP 7 Professional V12 (TIA Portal) or higher
identification & maintenance function	
I&M0 - device-specific information	Yes
I&M1 - higher level designation/location designation	Yes
product functions / diagnostics	
product function / web-based diagnostics	Yes; via S7-1500 CPU
product functions / time	
product function / pass on time synchronization	Yes
standards, specifications, approvals	
reference code	
according to IEC 81346-2:2019	KEC
standards, specifications, approvals / Environmental Product Declaration	
Environmental Product Declaration	Yes
global warming potential [CO2 eq]	
total	115.52 kg
during manufacturing	21.24 kg
during operation	93.93 kg
after end of life	0.35 kg
further information / internet links	
internet link	
to web page: selection aid TIA Selection Tool	https://www.siemens.com/tstcloud
to website: Industrial communication	https://www.siemens.com/simatic-net
to web page: SiePortal	https://sieportal.siemens.com/
to website: Image database	https://www.automation.siemens.com/bilddb
to website: CAX-Download-Manager	https://siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial cybersecurity functions that support the secure operation of plants, systems, machines and networks.

In order to protect plants, systems, machines and networks against cyber threats, it is necessary to implement – and continuously maintain – a holistic, state-of-the-art industrial cybersecurity concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial cybersecurity measures that may be implemented, please visit www.siemens.com/cybersecurity-industry. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Cybersecurity RSS Feed under <https://www.siemens.com/cert>. (V4.7)

Approvals / Certificates

General Product Approval



[Declaration of Conformity](#)



[China RoHS](#)

General Product Approval

For use in hazardous locations



[FM](#)

[CCC-Ex](#)

Environment



last modified:

2/18/2025 