



SIMATIC HMI KP8F PN, Key Panel, 8 short-stroke switches with multi-colored LEDs, PROFINET interfaces with PROFIsafe; 8 DI/DO and 2 safety DI pins, 24 V DC can be looped through parameterizable as of STEP 7 V5.5

General information	
Product type designation	KP8F PN
Control elements	
With parameterizable keys	Yes
Keyboard fonts	
- Membrane keyboard — user-definable label membrane keys - Function keys — Number of function keys - Short-stroke keys — Number of short-stroke keys	Yes 8 8
Expansions for operator control of the process	
- DP direct LEDs (LEDs as S7 output I/O) - Number of color modes for LED - Direct keys (keys as S7 input I/O)	8; Adjustable brightness 5; red, green, blue, yellow, white 8
Installation type/mounting	
Mounting type	Mounting clip
Mounting position	vertical
Rack mounting	No
Front mounting	Yes; Compatible with Extension Units dimensions
Rail mounting	No
Wall mounting/direct mounting	No
Mounting in portrait format possible	Yes
Mounting in landscape format possible	Yes
maximum permissible angle of inclination without external ventilation	30°; To the front/rear
Number of slots for command devices and signaling units	0
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V; 24 V can be looped through connector, interrupted when pulled
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	0.3 A
Digital inputs	
Number of digital inputs	8; total inputs and outputs max. 8 and 2x SIL 2 or 1x SIL 3
Input voltage	
Rated value (DC)	24 V
Digital outputs	
Number of digital outputs	8; Max. 8 inputs and outputs (total)

Short-circuit protection	Yes
Switching capacity of the outputs	
• with resistive load, max.	100 mA
Output voltage	
• Rated value (DC)	24 V; Non-isolated
Total current of the outputs	
• Current per channel, max.	100 mA
• Current per group, max.	800 mA
Interfaces	
Number of industrial Ethernet interfaces	2; For the construction of lines and rings without external switch
Number of PROFINET interfaces	2; Incl. switch
Industrial Ethernet	
• Industrial Ethernet status LED	2; Per port
• Number of ports of the integrated switch	2; Per port
Protocols	
PROFINET	Yes; also 3rd party PLC
Supports protocol for PROFINET IO	Yes
PROFINET CBA	No
IRT	Yes
PROFIsafe	Yes; 1x SIL 3 (two-channel) or 2x SIL 2 (single-channel) emergency stop sensors
PROFIBUS	No
EtherNet/IP	No
MPI	No
AS-Interface	No
EIB/KNX	No
Protocols (Ethernet)	
• TCP/IP	No
Redundancy mode	
Media redundancy	
— MRP	Yes
Further protocols	
• AS-Interface Safety at Work	No
• CAN	No
• Data-Highway	No
• DeviceNet	No
• DeviceNet Safety	No
• Foundation Fieldbus	No
• INTERBUS	No
• INTERBUS-Safety	No
• Local Operating Network	No
• MODBUS	No
• SafetyBUS p	No
• SERCOS	No
• SUCOnet	No
• other bus systems	No
Test commissioning functions	
Illuminant test	Yes; During switch on
Key and signal lamp test	Yes; automatically when switching on
EMC	
Emission of radio interference acc. to EN 55 011	
• Limit class A, for use in industrial areas	Yes; Group 1, measured at a distance of 10 m
• Limit class B, for use in residential areas	No
Degree and class of protection	
IP (at the front)	IP65
IP (rear)	IP20
NEMA (front)	
• Enclosure Type 4 at the front	No
• Enclosure Type 4x at the front	Yes; Incl. NEMA12
Standards, approvals, certificates	
CE mark	Yes

cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
CCC	No; not necessary
Suitable for safety functions	Yes
Use in hazardous areas	
• ATEX Zone 2	Yes
• ATEX Zone 22	Yes
• cULus Class I Zone 1	No
• cULus Class I Zone 2, Division 2	Yes
• FM Class I Division 2	Yes
Marine approval	
• Germanischer Lloyd (GL)	No
• American Bureau of Shipping (ABS)	No
• Bureau Veritas (BV)	No
• Det Norske Veritas (DNV)	No
• Lloyds Register of Shipping (LRS)	No
• Nippon Kaiji Kyokai (Class NK)	No
• Polski Rejestr Statkow (PRS)	No
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Operation (vertical installation)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	55 °C
Operation (max. tilt angle)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, max.	45 °C
Operation (vertical installation, portrait format)	
— For vertical installation, min.	0 °C
— For vertical installation, max.	55 °C
Operation (max. tilt angle, portrait format)	
— At maximum tilt angle, min.	0 °C
— At maximum tilt angle, max.	45 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	95 %; no condensation
configuration / header	
Configuration software	
• STEP 7 Basic (TIA Portal)	Yes
• STEP 7 Professional (TIA Portal)	Yes
Functionality under WinCC (TIA Portal)	
Process coupling	
• S7-1200	Yes; with ET 200pro CPU and ET 200S CPU
• S7-1500	Yes
• S7-200	No
• S7-300/400	Yes; with F-CPU: STEP 7 V11 SP1 (or higher) and Safety V11 (or higher) or SIMATIC STEP 7 Basic V11 (or higher)
• LOGO!	No
• WinAC	Yes
• SINUMERIK	No
• SIMOTION	No
• Allen Bradley (EtherNet/IP)	No
• Allen Bradley (DF1)	No
• Mitsubishi (MC TCP/IP)	No
• Mitsubishi (FX)	No
• OMRON (FINS TCP)	No

• OMRON (LINK/Multilink) • Modicon (Modbus TCP/IP) • Modicon (Modbus)	No																																							
	No																																							
	No																																							
Mechanics/material																																								
Enclosure material (front) • Plastic • Aluminum • Stainless steel	Yes No No																																							
Service life																																								
• Short-stroke keys (in switching cycles) • LEDs (ON period)	1 500 000 100 %																																							
Dimensions																																								
Width of the housing front	98 mm																																							
Height of housing front	155 mm																																							
Mounting cutout, width	67.7 mm; Max. thickness of mounting plate 2 - 6 mm																																							
Mounting cutout, height	129.7 mm																																							
Overall depth	49 mm; Incl. angled SIMATIC Ethernet connector																																							
Weights																																								
Weight (without packaging)	280 g																																							
Classifications																																								
	<table><tr><th></th><th>Version</th><th>Classification</th></tr><tr><td>eClass</td><td>14</td><td>27-33-02-04</td></tr><tr><td>eClass</td><td>12</td><td>27-33-02-04</td></tr><tr><td>eClass</td><td>9.1</td><td>27-33-02-04</td></tr><tr><td>eClass</td><td>9</td><td>27-33-02-04</td></tr><tr><td>eClass</td><td>8</td><td>27-24-23-05</td></tr><tr><td>eClass</td><td>7.1</td><td>27-24-23-05</td></tr><tr><td>eClass</td><td>6</td><td>27-24-23-05</td></tr><tr><td>ETIM</td><td>9</td><td>EC001415</td></tr><tr><td>ETIM</td><td>8</td><td>EC001415</td></tr><tr><td>ETIM</td><td>7</td><td>EC001415</td></tr><tr><td>IDEA</td><td>4</td><td>5266</td></tr><tr><td>UNSPSC</td><td>15</td><td>39-12-22-21</td></tr></table>		Version	Classification	eClass	14	27-33-02-04	eClass	12	27-33-02-04	eClass	9.1	27-33-02-04	eClass	9	27-33-02-04	eClass	8	27-24-23-05	eClass	7.1	27-24-23-05	eClass	6	27-24-23-05	ETIM	9	EC001415	ETIM	8	EC001415	ETIM	7	EC001415	IDEA	4	5266	UNSPSC	15	39-12-22-21
	Version	Classification																																						
eClass	14	27-33-02-04																																						
eClass	12	27-33-02-04																																						
eClass	9.1	27-33-02-04																																						
eClass	9	27-33-02-04																																						
eClass	8	27-24-23-05																																						
eClass	7.1	27-24-23-05																																						
eClass	6	27-24-23-05																																						
ETIM	9	EC001415																																						
ETIM	8	EC001415																																						
ETIM	7	EC001415																																						
IDEA	4	5266																																						
UNSPSC	15	39-12-22-21																																						
Approvals / Certificates																																								
General Product Approval																																								
EMV																																								
 EG-Konf.   UL KC  RCM  RCM																																								
For use in hazardous locations																																								
FM  ATEX  UL CCC-Ex FM  ATEX																																								
For use in hazardous locations	Functional Safety	Maritime application																																						
Miscellaneous	Type Examination Certificate																																							
 IECEX	 TUV	 ABS																																						
																																								
Maritime application																																								



[NK / Nippon Kaiji Ky-
okai](#)



[CCS \(China Classifica-
tion Society\)](#)



other	Industrial Communication
-------	--------------------------

[PROFINET](#)

[PROFIsafe](#)

[PROFINET](#)

last modified:

11/19/2024